



Optional jackets are available.



## Features & Benefits

Canature 565 water softeners offer the following features and benefits:

- Full electronics for more efficient and precise operation to reduce salt and water consumption.
- User-friendly programming and diagnostics.
- Ability to view operational data on our large LED display, without the need for a manual or use of confusing codes.
- Self-charging capacitor to keep track of time in the event of a power outage.
- Fully adjustable cycles for more efficient and effective operation.
- By-pass valve is included, using quick connect fittings.
- Quick connect fittings on brine line, drain line and power cord.
- Pre-loaded mineral tanks available for easy shipping.

By-pass valve with quick connect fittings is included.



Part Number	Pipe Size	Valve Type #565	Continuous Flow Rate (GPM at 15 psi drop)	Backwash Flow Rate (At 25 psi)	Master Ctn. Pack of 4 valves with by-pass	Shipping Weight Pack of 4 (Lbs.)
10010009	3/4" - 1"	Electronic	20	7	19x19x16	28

Pre-loaded mineral tanks (with resin, gravel and riser tubes installed for E-Z shipping).

Part Number	Tank Size	Tank Color	Resin (Cu. Ft.)	Gravel (Lbs.)	Number Per Carton	Carton Dimensions	Shipping Weight (Lbs.)
25020006	9x48	Black	1.0	10	1	10x10x51	77
25020005	9x48	Natural	1.0	10	1	10x10x51	77
25020010	10x54	Black	1.5	15	1	11x11x57	104
25020009	10x54	Natural	1.5	15	1	11x11x57	104

Note: Pressure vessels are NSF standard 44 certified and are rated for operating pressures to 150 psi (10 bar) and temperatures between 34°F-122°F.

Brine tanks with safety float, brine well and salt grids, packaged five per carton.

Part Number	Size	Color	Capacity (Gals.)	Shape	Number Per Carton	Master Carton (Five brine tanks)	Shipping Wt. Master Carton (Lbs.)
30020023	15" x 34"	Black	30	Square	5	16x16x61	70
30020021	15" x 34"	Vanilla	30	Square	5	16x16x61	70
30020011	20" x 37"	Black	42	Round	5	22x21x72	85
30020009	20" x 7.5"	Vanilla	42	Round	5	22x21x72	85

Note: Single brine tanks are available.